



Smart Look. Smart Choice.

Wanda 8100 2K Primer



Sometimes it's the things you don't see that are the most important. That's why you want a primer that's going to set the stage for your color. **Wanda 8100 2K Primer** is a polyurethane high build primer filler that offers good adhesion to properly prepared substrates. Its light gray color allows for easy topcoat coverage and optimal color appearance. With fast drying time, excellent sanding properties and durability, **Wanda 8100 2K Primer** is the *Smart Choice* to achieve that *Smart Look*.

Product Features

- Excellent filling properties
- Durability
- Easy to sand
- Good color holdout
- Easy application
- Fast drying
- Value-priced

Your Benefit

- Fills sand scratches quickly
- System approach with Wanda topcoat provides optimal durability
- Saves time and materials
- Gloss retention, customer satisfaction
- No special training needed
- Time savings
- Lower cost, great results



Smart Look. Smart Choice.



Wanda 8100 2K Primer

Description

A polyurethane high build primer filler with good adhesion to properly prepared substrates. It has fast drying time, great sanding properties and durability. It can be used as a high build primer or primer surface.

Product and Additives

Product - Wanda 8100 2K Primer

Hardener- Wanda 2K Hardener-Standard, Wanda 2K Hardener-Slow

Reducers - Wanda HS 2K Reducer


Mixing Ratio

High Build Filler

4 parts by volume Wanda 8100 2K Primer
1 part by volume Wanda 2K Hardener
10% Wanda HS 2K Reducer

Primer Surface

4 parts by volume Wanda 8100 2K Primer
1 part by volume Wanda 2K Hardener
20% Wanda HS 2K Reducer



Application Process

Apply 2 to 3 single coats.

Flash Time

Allow for 5-10 minutes flash time between coats.

Drying Times

Wanda 2K Hardener-Standard

	70°F (20°C)	140°F (60°C)
Cure time	2 - 3 hours	30 minutes

See the Wanda 8100 2K Primer complete Technical Data Sheet DW1 for more detailed product and application information.

WAN203 08/07

